

# Welding Fume Extractors

## Fume-Air™ 750

**Designed for Heavy Duty, Long Duration Welding**

The steel Fume-Air™ 750 HEPA filtered fume extractor provides 750 cfm flow through a 13" hood and is ideal for welding and soldering applications where large flow volume is required. With 270 degree movement and 10 foot arm length, it is easy to position the hood next to the welding work.

The pre-filter pad and certified HEPA filter remove 99.97% at 0.3 micron and meets the OSHA Permissible Exposure Limit (PEL) for hexavalent chromium of 5 µg/m³ and other toxic welding dusts.



**Fume-Air™ 750**  
PFE-750-8

### Key Details:

- Steel Cabinet
- 115 VAC motor, 12.5 amps, 1.0 HP
- Filter change indicator
- HEPA Filter, 99.97%, UL 129R flame rated, DOP tested, 1000 cfm flow rate
- 24" x 24" x 1" prefilter pad and holder
- 750 cfm flow with 10 foot arm
- 13 inch fume capture hood with adjustable flow damper - optional hood light
- 6 inch diameter, 10 foot adjustable arm with 270 degree movement
- Arm shipped assembled and ready to bolt on to main extraction cabinet
- Lift-up filter door for easy access filter change
- 5" Heavy duty casters

**Dimensions:** 27" W X 40" D X 32.5" H

**Weight:** 370 lbs



**Fume-Air™ 750 Filter Set-up**



### Fume-Air™ 750

Item No.	Description
PFE-750-8	115/230 VAC, 12.5 AMP, 1 HP, filter change indicator, 10 foot arm assembly, 6" diameter arm, 13" wide fume hood, 5" casters, prefilter pad, 99.97% HEPA filter

### Filters & Accessories

Item No.	Description
PFE-2412HF	HEPA filter (99.97%), 24" x 24" x 11.5" - Package of 1
PFE-2424PF	Prefilter pad, 24" x 24" x 1", package of 10
PFE-2424C	Charcoal impregnated prefilter pad, 24" x 24" x 1", package of 10