

Air-Light® and Air-Light® II Portable Area Lighting



Light Run Time (in Hours)



4000 Lumen
2 Light Heads



9500 Lumen
2 Light Heads



9800 Lumen
2 Light Heads

Air-Light®



22 Amp Battery

Air-Light® II



35 Amp Battery

Run Hours		
1 Head Operating	Configuration not offered	1 Head Operating
14+		7+
2 Heads Operating		2 Heads Operating
7+		4+
Run Hours		
1 Head Operating	1 Head Operating	1 Head Operating
25+	9+	9+
2 Heads Operating	2 Heads Operating	2 Heads Operating
14+	5+	5+

Light Head Configurations Available



4000 total lumens
2 amps, 24 watts



9500 total lumens
7.5 amps, 90 watts



9800 total lumens
6.65 amps, 80 watts

Light Head Specifications:

- IP-68 rated dustproof and waterproof
- 60° wide flood beam pattern
- Anodized aluminum frame with a polycarbonate lens
- Operating temperature: -40°F to 176°F (-40°C to 80°C)
- Lifetime warranty on light heads



Air Systems International, Inc.

E-Mail: Sales@airsystems.com

Toll Free: (800) 866-8100

Phone: (757) 424-3967

www.airsystems.com

Air-Light® and Air-Light® II Portable Area Lighting

Air-Light® DC powered Portable Area Lighting Systems are designed to provide high power LED lighting for both indoor and the most adverse outdoor conditions. The compact portable design comes fully assembled for use and deploys rapidly in under 30 seconds without the need for component assembly. A stable platform ensures reliable lighting on rugged terrain and in high wind conditions. **All lights can be used in dusty & wet environments!**

Fully Extends to 87" Height



Air-Light®
AL9800BP



Applications

- Area Lighting
- Construction & Maintenance
- Utility Work
- Emergency Response Lighting
- Crime Scene Investigation
- Power Outages
- Hospital Triage
- Flagger Lighting
- Emergency Response Lighting

Fully Extends to 8' Height



Air-Light® II
AL2-4K-35

Portable Area Lighting Product Line

The Air-Light®

Model No.	Description
AL4KBP	Air-Light®, LED lights, 4000 total lumens
AL9800BP	Air-Light®, LED lights, 9800 total lumens

All Air-Light® models include 22 amp battery, internal 3 amp battery charger, and charging cables



WARNING: This product contains a sealed lead acid battery which can expose you to chemicals including Lead and Sulfuric Acid, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov.

The Air-Light® II

Model No.	Description
AL2-4K-35	Air-Light® II, LED lights, 4000 total lumens
AL2-95-35	Air-Light® II, LED lights, 9500 total lumens
AL2-98-35	Air-Light® II, LED lights, 9800 total lumens

All Air-Light® II models include 35 amp battery, internal 3 amp battery charger, and charging cables

Please consult the Master Catalog for additional details and specifications.