

Why Use the Blast-Air™ Cart?

The Blast-Air™ Cart has been designed to meet the demanding needs of the sandblast and coatings industry. The Blast-Air™ Cart features two 300 cfm rear pre-filters with auto-drains to remove large amounts of oil and water discharged from a compressor before it enters the Breather Box®. The pre-filters will extend the Breather Box® filter life and reduce maintenance downtime and costs. Air is supplied to the cart from mobile or fixed air compressors.



Portable Grade-D Air Filtration - The Blast-Air™ Cart

Model No.	Description
BA-30	30 cfm Breather Box® installed on the Blast-Air™ Cart, 48 cfm flow capacity, 2 couplings
BA-50	50 cfm Breather Box® installed on the Blast-Air™ Cart, 79 cfm flow capacity, 4 couplings
BA-100	100 cfm Breather Box® installed on the Blast-Air™ Cart, 123 cfm flow capacity, 4 couplings
BA-100-6	100 cfm Breather Box® installed on the Blast-Air™ Cart, 123 cfm flow capacity, 6 couplings
BA-100-8	100 cfm Breather Box® installed on the Blast-Air™ Cart, 123 cfm flow capacity, 8 couplings
BA-1CAA	Cart only with rear filters & connect hose, customer mounts existing Breather Box®
BB100-A	Replacement Pre-filters for Blast-Air™ Cart, sold each

Please specify 1/4" Hansen style or Schrader style fittings when ordering. Other fittings available for an additional charge - see page 92 for information.



All Blast-Air™ carts are available with an optional CSA approved intrinsically safe CO or CO/O₂ Monitor.



See Page 16 for Calibration Kit Ordering Information and Page 15 for Replacement Filters

