Grade-D Breathing Air Filtration



POA-5RF

A POA consists of a regulator, pressure gauge, safety relief valve, and fitting congruency necessary for proper respirator operation. A POA box can be located any distance from the Grade-D filtration Breather Box[®] or filtration panel. The remote air manifold (POA) assembly becomes the NIOSH attachment point for the respirator(s) and is now limited to a maximum 300 feet of breathing air hose at the air outlet fitting on the remote POA box. POA boxes may be taken into wet and/or hazardous locations. **All our remote air manifolds meet NIOSH requirements of the 87-116 (1989) document for point of attachment.**

Portable Point of Attachments (POA)

Item No.	Description
POA-2	Standard POA Box - 2 couplings
POA-4	Standard POA Box - 4 couplings
POA-4R	POA Box with 4 independent regulators & couplings
POA-4F	POA Box with final particulate filter & 4 couplings
POA-5RF	POA Box with final particulate filter and 5 independent regulators
POA-X	Custom POA Box - Contact Customer Service for ordering details

Optional Custom Designed POA Options

- Clear view window over gauge
- Multiple filters and independent regulators
- Stainless steel or aluminum panels
- Low pressure warning alarms
- Models available for 1-8 workers
- High pressure applications

Wall Mounted Point of Attachments (POA)

Item No.	Description
POA-1WM	Wall mounted POA manifold - 1 coupling
POA-2WM	Wall mounted POA manifold - 2 couplings
POA-4WM	Wall mounted POA manifold - 4 couplings
POA-4FWM	Wall mounted POA manifold with final particulate filter & 4 couplings
POA-XWM	Custom wall mounted POA manifold - Contact Customer Service
	for ordering details

Specify 1/4" Hansen style or Schrader style respirator fittings when ordering. Other fittings available for an additional charge. See page 90 for fittings.

