THE GOOL BOX TM Portable Cooling Air Distribution Manifold





Heat Stress Prevention

Key Details:

- · Low cost cool breathing air
- 50°F output air temperature with input up to 180°F
- · Easy to use and maintain manual drain provided
- · Aluminum jacketed tubing, USDA approved
- · 20 lbs. of ice provides up to 4 hours of cooling
- NIOSH point-of-attachment and cooling in one system
- Operates with any airline mask or hood style respirator, including level "A" chemical suits & abrasive blasting hoods
- Low pressure COOL-BOX™ for use with ambient air pumps, 0-20 psi maximum
- Standard GOOL-BOX[™] for all airline respirators 20-120 psi supplied with Grade-D air



Applications

- Paining or Blasting
- Confined Space
- Utility Companies
- Maintenance
- Construction
- Production
- Level A Suits

THE GOOL-BOX TM

Item No.	Description
BACB-196 BACB-196LP	Standard COOL-BOX™ with ¼″ Hansen or Schrader style fittings - rated to 125 psi maximum inlet pressure Low Pressure COOL-BOX™ with ¼″ Hansen or Schrader style fittings. Designed specifically for use with ambient air pumps (0-20 psi maximum), low pressure air pump conversion kit (BACB-196K) included