

Saddle Vent® Special Application Devices

Tank Saddle Vent®

The Tank Saddle Vent® is designed for ship and tank applications and fits small round and oval entry ports 20" and smaller. **DOD approved for US Navy use.**



Tank Saddle Vent®

Item No.	Description
SV-189T	8" Tank Saddle Vent®, grey, 32" H x 13" W x 5" D
SV-90T	90° elbow to fit 8" Tank Saddle Vent® - grey

Designed to fit 18"W x 20"L oval shipboard hatch openings



8" 90° elbow
SV-90T

8" Tank Saddle Vent®
SV-189T



8" Saddlator™
SV189-29

The Saddlator™

Pneumatic Powered 8" Conductive Saddle Vent® Blower

The Saddlator™ provides positive or negative pressure ventilation for confined space entry operations in large work areas or tanks and is ideal for hazardous environments.

The Saddlator™

Item No.	Description
SV189-29	Saddlator™ with elbow, positive pressure flow
SV189-29-N	Saddlator™, negative pressure flow
SV90-29	90° bolt-on elbow to fit Saddlator™
SV189T-29	Tank Saddlator™, with elbow, positive pressure flow
H-50-5	1/2" compressor connect hose – 50 foot
H-50-12	3/4" compressor connect hose – 50 foot

The Saddlator™

- Conductive Saddle Vent® with Venturi base installed
- 90° bolt-on conductive elbow, SV90-29, supplied
- Air operated, no moving parts
- 1/2" Industrial Interchange plug
- Static ground lug installed
- Delivers 2000-3000 cfm on pressures from 50-100 psi
- 8" Inlet and Outlet

Saddle Vent® is a Registered Trademark of Air Systems International, Inc.

