Confined Space Ventilation



8" Centrifugal Blowers for Hazardous Locations

Item No.	Description
SVB-E8EXP SVB-E8X250 SVB-A8	Explosion-proof electric motor - 3/4 HP, 115 VAC, 12.6 amp, 72 lbs. Plug not included. Explosion-proof electric motor - 3/4 HP, 220 VAC, 50 Hz, 78 lbs. Plug not included. Pneumatic motor - 4 HP, operates from 10-100 psi. Includes moisture / oil separator and filter, 61 lbs.

Plug sold separately. No additional labor charge for installation prior to shipment.

Approved for Hazardous Location Usage:

SVBE8EXP - CSA C/US certified for Classes I and II, Groups C, D, E, F, and G.

Explosion-Proof Electric Blower Kit

Item No.	Description
SVB-E8XCUP	Explosion-proof electric blower (SVB-E8EXP) and Conductive Kit SV-CUPCND,
	Plug not included. Order plug below.
SVB-A8CUP	Intrinsically Safe pneumatic blower (SVB-A8) and Conductive Kit SV-CUPCND
SV-CUPCND	Conductive Blower Kit: Conductive Saddle Vent®, 90° conductive elbow,
	6 and 15 foot conductive duct, duct canister, and universal mount

Plug sold separately. No additional labor charge for installation prior to shipment.

Explosion-Proof Plugs

Item No.	Description
ELAP15231	15 AMP, 125 VAC, EXP plug w/quick wiring (5-15P) USA / Canada
ELAP20231	20 AMP, 125 VAC, EXP plug w/quick wiring (5-20P) USA / Canada
ELAP15232	15 AMP, 250 VAC, EXP plug w/quick wiring (6-15P) International
ELAP20232	20 AMP, 250 VAC, EXP plug w/quick wiring (6-20P) International

No additional labor charge for installation prior to shipment.

Explosion-Proof Plugs



