



Custom Duct Transitions

Enlarging and Reducing Adapters are Available to Accommodate Any Transition Size - Contact Customer Service for Ordering Information.

Electric Ventilation Heaters



Ventilation Heater
SVF-15KW-8

32" L X 27" H X 37.5" W
95 lbs.

All electric heaters are available with duct size flanges - specify size when ordering

Key Details:

- Heaters operate with blower or fan only
- 8" inlet and exhaust flanges
- Aluminum frame with control box
- Automatic start with blower running
- Built-in safety pressure switch
- Automatic thermal shutdown at 170°F
- 144°F output at exhaust, 112°F with 15 foot duct



Ventilation Heater
SVF-7KW-8

27" L X 16" H X 15.5" W
40 lbs.

Ventilation Heater - 8" Duct Flange

Item No.	Description
SVF-7KW-8	8" Electric ventilation heater, 7kw, 230/1 VAC, 28 amps, 23,900 BTU - 30 amp plug
SVF-10KW-8	8" Electric ventilation heater, 10kw, 440/3 VAC, 15 amps, 34,145 BTU - user wired
SVF-15KW-8	8" Electric ventilation heater, 15kw, 440/3 VAC, 26 amps, 51,216 BTU - user wired

Vent Flow™ Alarm

Meets Confined Space Ventilation Flow Loss Alarm Requirements



Vent Flow™
Alarm in Use
SVF-8ALM



Vent Flow™
Alarm
SVF-8ALM

Key Details:

- Models available for 8" or 12" blower duct (other sizes available)
- For best results, use 6 foot duct (SVH-6), to connect from blower to Vent Flow™
- No AC power required - operates on two 9 VDC batteries
- Audible alarm (92 dBA) and visual red light activate with approximately 50% flow loss in the duct
- Alarms deactivate when normal flow is re-established
- Galvanized tubular steel housing
- Meets Canadian alarm requirements
- Overall length: 13"

Vent Flow™ Alarm

Item No.	Description
SVF-8ALM	Vent-Flow™ Alarm, 9 VDC, galvanized, 8" inlet/outlet, 7 lbs.
SVF-12ALM	Vent-Flow™ Alarm, 9 VDC, galvanized, 12" inlet/outlet, 12 lbs.

For Use In Non-Hazardous Locations