

AIR LIGHT - II™

Dual Cube Dimensions & Specifications:

1800 Lumen Output For Use In Any Weather!

Operational Features:

- Weatherproof - can be used in dusty & wet environments!
- Light cubes IP-68 rated dustproof and waterproof!
- Collapsible aluminum extension mast with cam lock adjustments and retractable cable
- Can be operated from internal battery or external 12 VDC power through DC power port or jumper cables without interrupting light operation
- Push-to-Test digital volt meter on front panel
- 12V DC power port for quick charge from an external battery source and/or run 12V devices such as cell phones, laptops, and/or handheld lights
- Charge with clamp style jumper cables or 110-240 VAC, 50/60 Hz power
- Independent directionally adjustable light heads
- Jump start vehicle with clamp style jumper cables
- Retracting legs offer support on uneven terrain
- Separate LED flasher light for added visibility
- Mast range 24" to 96" (8') above ground

Internal Battery:

- 12 VDC sealed 35 amp hour AGM lead acid battery
- Built in 110-240 VAC, 50/60 Hz, UL approved 3 amp charge system
- Safely stored/operated at -40°F to 140°F (-40°C to 60°C)
- 24 hour recharge when fully depleted
- Rated for 500+ charge cycles
- One year replacement warranty on battery and charger

Light Cube Specifications:

- 60° beam pattern
- Anodized aluminum frame with polycarbonate lens
- Operating temperature: -40°F to 176°F (-40°C to 80°C)
- Lifetime warranty on light heads

Dimensions

Width: 17.5"

Depth: 8"

Height: 25"

Height with mast fully extended: 8' (96")

Leg extension:

16" providing 32" diameter base

Weight: 41 lbs.

US and Foreign
Patents Pending



Dual Cube Specifications:

- 1800 lumens
- 1.5 amps, 20 watt
- Full Charge Run Time:
 - 16+ Hours running 1 light head
 - 8+ Hours running 2 light heads



Air Light-II™ Dual
Model AL2-2-35
1800 Lumens

Air Systems International, Inc.

E-Mail: Sales@airsystems.com

Web: www.airsystems.com

Toll Free: (800) 866-8100

Phone: (757) 424-3967