

# Air-Light® and Air-Light® II Portable Area Lighting



## Light Run Time (in Hours)



4000 Lumen  
2 Light Heads



7400 Lumen  
2 Light Heads



9800 Lumen  
2 Light Heads

Air-Light®



22 Amp Battery

Air-Light® II



35 Amp Battery

Run Hours		
1 Head Operating	Configuration not offered	1 Head Operating
<b>14+</b>		<b>7+</b>
2 Heads Operating		2 Heads Operating
<b>7+</b>		<b>4+</b>
Run Hours		
1 Head Operating	1 Head Operating	1 Head Operating
<b>25+</b>	<b>10+</b>	<b>9+</b>
2 Heads Operating	2 Heads Operating	2 Heads Operating
<b>14+</b>	<b>5+</b>	<b>5+</b>

## Light Head Configurations Available



**4K**

4000 total lumens  
2 Lights per Unit  
2 amps, 24 watt



**XP**

7000 total lumens  
2 Lights per Unit  
5.8 amps, 70 watts



**8600**

9800 total lumens  
2 Lights per Unit  
6.65 amps, 80 watts

### Light Head Specifications:

- IP-68 rated dustproof and waterproof
- 60° wide flood beam pattern
- Anodized aluminum frame with a polycarbonate lens
- Operating temperature: -40°F to 176°F (-40°C to 80°C)
- Lifetime warranty on light heads



### Air Systems International, Inc.

E-Mail: Sales@airsystems.com

Toll Free: (800) 866-8100

Phone: (757) 424-3967

[www.airsystems.com](http://www.airsystems.com)

# Air-Light® and Air-Light® II Portable Area Lighting

Air-Light® DC powered Portable Area Lighting Systems are designed to provide high power LED lighting for both indoor and the most adverse outdoor conditions. The compact portable design comes fully assembled for use and deploys rapidly in under 30 seconds without the need for component assembly. A stable platform ensures reliable lighting on rugged terrain and in high wind conditions. **All lights can be used in dusty & wet environments!**



**Air-Light®**  
AL8600BP



**Air-Light® II**  
AL2-2K-35

## Portable Area Lighting Product Line

### Air-Light®

Model No.	Description
AL4KBP	Air-Light® 4K, 4000 total lumens
AL8600BP	Air-Light® 8600, 9800 total lumens

**All models include 22 amp battery, internal 3 amp battery charger and charging cables**

### Air-Light® II

Model No.	Description
AL2-4K-35	Air-Light® II 4K, 4000 total lumens
AL2-7-35	Air-Light® II XP, 7000 total lumens
AL2-86-35	Air-Light® II 8600, 9800 total lumens

**All models include 35 amp battery, internal 3 amp battery charger, and charging cables**

Please consult the Master Catalog for additional details and specifications.



**WARNING:** This product contains a sealed lead acid battery which can expose you to chemicals including **Lead** and **Sulfuric Acid**, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

Product and training videos at [www.airsystems.com](http://www.airsystems.com)