

## The Auto-Air™ Cart

The Auto-Air™ Cart contains an Auto-Air™ Breather Box® to provide Grade-D breathing air while continuously monitoring for Carbon Monoxide (CO). In the event of electrical failure or air pressure failure, the reserve air activation automatically switches to the reserve air cylinder(s). A pneumatic or electronic reserve air system consisting of twin air cylinders provides back-up air. Select the cart size based on the desired amount of users and reserve air needed to allow workers to safely egress the work area in an emergency. **Carts operate with 2216 to 5000 psi cylinders (sold separately).**

### Key Details:

- Primary Air Line, ½" Inlet - Hansen 5000 Style Fitting
- Reserve Air Line, ¼" Inlet - Hansen 3000 Style Fitting
- Carbon Monoxide (CO) Monitor
- **CO/O<sub>2</sub> Monitors also Available**
- **Intrinsically Safe CO/O<sub>2</sub> Monitors also Available on Pneumatic Models**
- Filter Change Indicators on All Filters
- 2 Automatic Drains with Discharge Tubes
- Remote Alarm Jack Receptacle (Remote Alarm Optional)
- External Warning Lights and Alarm
- Reserve Cylinders Sold Separately
- Steel Cart
- Storage Box with Latch
- Pneumatic Tires



Large Cylinder Auto-Air™ Cart  
Pneumatic Reserve Air System  
BB100HTAAP



Small Cylinder Auto-Air™ Cart  
Pneumatic Reserve Air System  
BB50-HTAAP