

Cascade Breathing Air Assemblies


Air Systems' breathing air assemblies offer a complete system for use with airline respirators. Additional cylinder connecting whips can be added to extend breathing air capacity with additional cylinders. **Cylinders sold separately - see page 38.**



CBA3-347NB




RG-3000




RG-5000-2Y



HP-CW1-347




POA-2HPWM




SS347HT



SS347SNHT



SS702N
and SS702S



HPBR049
and HPBR050

Cascade Breathing Air Assemblies

Item No.	Description
CBA3-346NB	3 cylinder breathing air assembly, CGA-346, 3000 psi
CBA3-347NB	3 cylinder breathing air assembly, CGA-347, 5000 psi
CBA3-702NB	3 cylinder breathing air assembly, CGA-702, 6000 psi

Cylinders sold separately. See page 38. Please specify fittings when ordering.

Additional breathing air assemblies and low pressure bell alarm options available. Contact Customer Service.

Assemblies include regulator, 4-outlet manifold, low pressure alarm whistle, relief valve, and connecting whips with check valves.

Breathing Air Regulators & Manifolds

Item No.	Description
Breathing Air Regulators (1/4" QD Fitting)	
RG-3000	CGA-346, 3000 psi, adjustable regulator, dual gauges, and relief valve
RG-3000-2Y	RG-3000 regulator with 2 fittings, includes check valve and low pressure alarm whistle, 3000 psi, CGA-346
RG-5000	CGA-347, 5000 psi, adjustable regulator, dual gauges, and relief valve
RG-5000-2Y	RG-5000 regulator with 2 fittings, includes check valve and low pressure alarm whistle, 5000 psi, CGA-347
RG-6000	CGA-702, 6000 psi, adjustable regulator, dual gauges, and relief valve
Breathing Air Manifolds	
HP-CW1-346	4-outlet manifold assembly with safety relief valve, 3000 psi regulator, CGA-346 connection, low pressure alarm whistle, 4 fittings
HP-CW1-347	4-outlet manifold assembly with safety relief valve, 5000 psi regulator, CGA-347 connection, low pressure alarm whistle, 4 fittings
HP-CW1-702	4-outlet manifold assembly with safety relief valve, 6000 psi regulator, CGA-702 connection, low pressure alarm whistle, 4 fittings

High Pressure Point of Attachments (POA)

Item No.	Description
POA-2HPWM	Wall mounted high pressure POA manifold, 5000 psi - 2 couplings

Contact Customer Service to order custom wall mounted POA's

High Pressure CGA Fittings

Hand Tight Fitting

Item No.	Description
SS347HT	CGA-347 universal hand-tight, fits CGA-346 or 347 male thread, maximum pressure 5500 psi, gold
SS347SNHT	CGA-347 high pressure hand-tight, fits CGA-347 male thread only, maximum pressure 5500 psi, silver

Wrench Tight Fittings

Item No.	Description
HPBR025	CGA-346 brass nut - max pressure 3000 psi
HPBR026	CGA-346 brass stem - max pressure 3000 psi
HPBR027	CGA-346 brass stem with check valve - max Pressure 3000 psi
HPBR049	CGA-347 brass nut - max pressure 5500 psi
HPBR050	CGA-347 brass stem - max pressure 5500 psi
SS702N	CGA-702 brass nut - max pressure 7500 psi
SS702S	CGA-702 brass stem - max pressure 7500 psi