BB50-CO
50 cfm Breather Box®
79 cfm flow capacity
4 couplings

BB75-CO Series
75 cfm Breather Box®
97 cfm flow capacity
4 to 6 couplings available

BB100-CO Series
100 cfm Breather Box®
123 cfm flow capacity
4 to 8 couplings available

Portable Grade-D Breathing Air Filtration with CO Monitor

Item No.	Description
BB15-CO	15 cfm Breather Box®, 48 cfm flow capacity, 1 coupling
BB30-CO	30 cfm Breather Box®, 48 cfm flow capacity, 2 couplings
BB30-CO3	30 cfm Breather Box®, 48 cfm flow capacity, 3 couplings
BB50-CO	50 cfm Breather Box®, 79 cfm flow capacity, 4 couplings
BB75-CO4	75 cfm Breather Box®, 97 cfm flow capacity, 4 couplings
BB75-CO6	75 cfm Breather Box®, 97 cfm flow capacity, 6 couplings
BB100-CO	100 cfm Breather Box®, 123 cfm flow capacity, 4 couplings
BB100-CO6	100 cfm Breather Box®, 123 cfm flow capacity, 6 couplings
BB100-CO8	100 cfm Breather Box®, 123 cfm flow capacity, 8 couplings
BB150-CO	150 cfm Breather Box®, 203 cfm flow capacity, three ½″ industrial interchange couplings Requires use of a Point of Attachment (pages 17-18)
	International Power Source - Call Customer Service for additional information
BB30-CO220	30 cfm Breather Box®, 48 cfm flow capacity, 2 couplings, 220 VAC 50 Hz, specify cord
BB50-CO220	50 cfm Breather Box®, 79 cfm flow capacity, 4 couplings, 220 VAC 50 Hz, specify cord

2 YEAR WARRANTY ON CO SENSOR & MONITOR

Specify 1/4" Hansen style or Schrader style respirator couplings when ordering. Other couplings available for an additional charge.

Portable Grade-D Breathing Air Filtration with CO/O₂ Monitor

Item No.	Description
BB30-COO2	30 cfm Breather Box®, 48 cfm flow capacity, 2 couplings
BB50-COO2	50 cfm Breather Box®, 79 cfm flow capacity, 4 couplings
BB75-COO2	75 cfm Breather Box®, 97 cfm flow capacity, 6 couplings
B100-COO2	100 cfm Breather Box®, 123 cfm flow capacity, 4 couplings

Breather Box® with 4 Independent Regulators BB50-CO4R

Portable Grade-D Breathing Air Filtration with CO Monitor and Independent Regulators

Item No.	Description
BB30-CO2R	30 cfm Breather Box®, 48 cfm flow capacity, 2 independent regulators & pressure gauges, 2 couplings
BB50-CO4R	50 cfm Breather Box®, 79 cfm flow capacity, 4 independent regulators & pressure gauges, 4 couplings
BB75-CO4R	75 cfm Breather Box®, 97 cfm flow capacity, 4 independent regulators & pressure gauges, 4 couplings
BB100-CO4R	100 cfm Breather Box®, 123 cfm flow capacity, 4 independent regulators & pressure gauges, 4 couplings

Portable Grade-D Air Filtration with Intrinsically Safe (IS) CO Monitor

Item No.	Description
BB15-COIS	15 cfm Breather Box®, Intrinsically Safe, 48 cfm flow capacity, 1 coupling
BB30-COIS	30 cfm Breather Box®, Intrinsically Safe, 48 cfm flow capacity, 3 couplings
BB50-COIS	50 cfm Breather Box®, Intrinsically Safe, 79 cfm flow capacity, 4 couplings
BB75-COIS	75 cfm Breather Box®, Intrinsically Safe, 97 cfm flow capacity, 4 couplings
BB100-COIS	100 cfm Breather Box®, Intrinsically Safe, 123 cfm flow capacity, 4 couplings

CSA® Approved for Class I, Division 1, Groups C and D environments (9 VDC operation only)

For Use In Hazardous Locations

Remote Alarms Available on Page 20

Contact Customer Service for custom options

Don't forget replacement filters and monitor calibration kit! See pages 21-22 for ordering information